

LEUPOLD® VX®-6

3-18x44mm Side Focus CDS Illuminated Riflescope



Legendary Leupold® durability, ruggedness, and stunning optical quality—times six. With a powerful 6:1 zoom ratio, the Leupold VX®-6 delivers crystal-clear images from edge-to-edge throughout the entire magnification range. Leupold's Quantum Optical System™ with legendary Xtended Twilight lens coatings and DiamondCoat 2™ combined with edge blackened lead-free lenses for astonishing clarity and light transmission. The extreme fast-focus eyepiece ensures a generous eyepiece, superior field of view, and optimal diopter adjustment in the field. Illuminated reticle on VX-6 models feature either traditional or super bright FireDot™ illumination. The 1-button low-profile design allows users to choose between 12 intensity settings. Proprietary motion sensor technology (MST™) automatically deactivates illumination after five minutes of inactivity, yet re-activates as soon as any movement is detected.

A rugged 30mm maintube, Twin Bias Spring Erector System™, and pop-up re-zero finger click adjustments assure maximum adjustment range and precision. All Leupold VX-6 riflescopes are CDS® capable and include one free Custom Ballistic Dial with purchase. Leupold Argon/Krypton second generation waterproofing resists the effects of thermal shock much more efficiently than standard nitrogen. Waterproof, shockproof, and backed by the Leupold Full Lifetime Guarantee/Leupold Golden Ring® Electronics Warranty, the Leupold VX-6 sets the standard for riflescope performance.

Reticle	FireDot™ Duplex® (CDS®)	Illuminated Boone and Crockett® Big Game (CDS)
Item Number & Finish	115002 (Matte)	115004 (Matte)
Lens Coating	Xtended Twilight, DiamondCoat 2™, and Edge Blackened Lenses	
Adjustment Markings	Finger-Adjustable, Pop-up resettable (or rezero), 1/4-MOA per click or 1cm per click	
Maintube Diameter	30mm	
Special Features	Superior 6:1 zoom optical system; Lead-Free Optical Design; Proprietary Motion Sensor Technology (MST™); FireDot™ Illumination; Light weight, compact, and durable	
Environmental Protection	2nd Generation, Waterproof, Fog Proof	
Eyepiece Design	Extreme Fast-Focus	
Actual Magnification	3.0-18.0	
Linear Field of View (ft @ 100yd)	75.9-13.7	
Linear Field of View (m @ 100m)	25.3-4.6	
Exit Pupil (mm)	10.0-2.4	
Weight (ounces)	19.2	
Weight (grams)	544	
Length (in)	13.5	
Length (cm)	34.2	
Mounting Space (in)	5.4	
Mounting Space (cm)	13.6	
Objective Aperture (mm)	44	
Eye Relief (in)	3.7-3.7	
Eye Relief (mm)	94.6-94.6	
Elevation Adjustment Range (MOA)	75	
Windage Adjustment Range (MOA)	75	



©2012 Leupold & Stevens, Inc.
 PO Box 688, Beaverton, OR 97075-0688
 14400 NW Greenbrier Parkway, Beaverton, OR 97006-5790 USA 10-1-12
www.leupold.com



AMERICA'S
 OPTICS
 AUTHORITY®